



Belt Name:

Part #:

APF B 940 SD (FMB 4 SD) 08-012

Technical Data

Color	Blue
Compound	PU
Plies	N/A
Fabric/Carcass	N/A
Cover Surface	Smooth
Hardness	95 Durometer
Bottom Surface	Positive Drive
Coefficient/Friction	0.5
Working Strength	45#
Overall Gauge	.157"
Including Lugs	.472"
Weight per Sq Ft	1.1
Minimum Pulley	
Normal-180°	3.75" Back Flex 6"
Temp Range °F	-5 to 140 F
Food Approved	3A Dairy
Anti-Static	No
Recommended Splice	Butt Weld
Clipper Lace	NA
Alligator Lace	NA
MD Splice	Yes
Maximum Width	80"

Features/Benefits:

Resistant to sodium hypochlorite at 5%, sodium hydroxide at 46-1/2%, sodium chloride solutions, soap solutions, trisodium phosphate solutions, mineral oil, ammonium chloride solutions. No strings. Cleans easily. Heavy chemical washdown resistance. Flexible. Easily installed endless. Can be custom fabricated to many specifications. Used mostly in direct food handling applications: poultry, beef and pork parts, grated or shredded cheese, pasta, dough, vegetable inspection tables. Additional benefit of Positive Drive material is that no system tension is required for operation.