



Belt Name:

3 Ply 330 SBR 3/16 x 1/16

Part #:

39S31/02-012

Technical Data

Color	Black		
Compound	SBR Styrene-butadiene		
Plies	3		
Fabric/Carcass	Polyester/Nylon		
Cover Surface	3/16" Smooth		
Hardness	60 Duro		
Bottom Surface	1/16" Smooth		
Working Strength	330		
Overall Gauge	0.405", 13/32", 10.3mm		
Weight per Sq Ft	2.5		
Minimum Pulley	60-80% tension	Back Flex	60-80% tension
Normal-180°	12"		12"
Temp Range °F	-20 to 250		
Food Approved	N		
Anti-Static	N		
Recommended Splice	Laced 140, 190, R2, R5, 550	Vulcanized Step length (bias)	6-8"
Clipper Lace	N/A		
Alligator Lace	N/A		
Maximum Width Available	84"	Maximum Width Stocked	60"

Features/Benefits:

General purpose abrasion resistant belting used to carry items such as stone, sand, lump materials, recyclables, or material that requires abrasion resistant belting. Common industries: Crushed Stone, Concrete Recycle Processor, Brick and Block Production. Not good for oily applications. Good abrasion resistance. Recommend use on roller bed conveyors.



COVER



BOTTOM

D&D Belt Service Phone (800) 799-0116 info@ddbeltservice.com www.ddbeltservice.com
Sparks Belting Company Phone (800) 451-4537 Fax (800) 338-2358 www.sparksbelting.com