



Belt Name:
M/F BP 290H QW FR


Part #:

Technical Data

Color	Black		
Compound	PVC		
Plies	2		
Fabric/Carcass	Extra Rigid Polyester		
Cover Surface	Longitudinal Ribs		
Hardness	45 Durometer Shore A		
Bottom Surface	Quiet Weave		
Coefficient/Friction	.22 on Steel		
Strength	13 N/mm @ 1%		74# @ 1%
Overall Gauge	.1535"		
Weight per Sq Ft	.8397#		
Minimum Pulley			
Normal-180°	3"	Back Flex	3.9"
Temp Range °F	20° to 175° F		
Food Approved	No		
Anti-Static	Yes		
Flame Retardant	ASTMD 378-10		
Recommended Splice	SFL		
Clipper Lace	Clipper G005		
Alligator Lace	RS62		
Maximum Width	78"		

Features/Benefits:

Excellent cross-width rigidity for the most demanding logistics applications including: telescoping, incline, and decline, and high speed applications. Ultra quiet design with thick PVC continuous top cover combined with quiet weave bottom fabric. ASTMD 378-10 Flame Retardant and REACH Compliant.



Phone: (800) 451-4537 Fax: (800) 338-2358 www.sparksbelting.com

8/20/2021