



Belt Name:
Sparlon 3E QM Grey

Part #:
04-700

Technical Data

Color	Grey		
Compound	Elastomer		
Plies	1		
Fabric/Carcass	Polyester		
Cover Surface	Elastomer		
Hardness	75 Durometer Shore A		
Bottom Surface	Elastomer		
Recommended elongation at fitting	.3 to 2%		
Working Strength	114# @ 1%		
Overall Gauge	.118"		
Weight per Sq Ft	.69#		
Minimum Pulley	Normal-180°	1.18"	Back Flex 1.18"
Temp Range °F	-4°F to 176°F		
Food Approved	No		
Anti-Static	Yes		
Recommended Splice	Finger		
Clipper Lace	N/A		
Alligator Lace	N/A		
Maximum Width	19.6"		

Features/Benefits:

Excellent resistance to oils, inks, chemicals and abrasion. This belt is non-marking, offers permanent antistatic characteristics and provides high flexibility and dimensional stability. The quick finger splice is ideal for applications where downtime must be kept to an absolute minimum. Ideal for folder gluer machines and production lines in the corrugated industry. Also suited for printing industry and tube winder applications in the corrugated industry. Commonly used on Flexo Folder Gluers.



Phone: (800) 451-4537 Fax: (800) 338-2358 www.sparksbelting.com