



Belt Name:
Sparlon 4P Grey

Part #:
04-705

Technical Data

| | | | |
|-----------------------------------|---|-------|-----------------|
| Color | Grey | | |
| Compound | Elastomer | | |
| Plies | 1 | | |
| Fabric/Carcass | Nylon | | |
| Cover Surface | High Abrasion Resistant Rubber Fabric Top Pattern | | |
| Hardness | 75 Durometer Shore A | | |
| Bottom Surface | High Abrasion Resistant Rubber Fabric Top Pattern | | |
| Recommended elongation at fitting | 1.5 to 3% | | |
| Working Strength | 57# @ 1% | | |
| Overall Gauge | .157" | | |
| Weight per Sq Ft | .88# | | |
| Minimum Pulley | Normal-180° | 1.57" | Back Flex 1.57" |
| Temp Range °F | -4°F to 176°F | | |
| Food Approved | No | | |
| Anti-Static | Yes | | |
| Recommended Splice | Skive | | |
| Clipper Lace | N/A | | |
| Alligator Lace | N/A | | |
| Maximum Width | 19.6" | | |

Features/Benefits:

Excellent resistance to oils, inks, chemicals and abrasion. This belt is non-marking, offers permanent antistatic characteristics and provides high flexibility and dimensional stability. Ideal for folder gluer machines and production lines in the corrugated industry. Also suited for printing graphic industry and tube winder applications.



Phone: (800) 451-4537 Fax: (800) 338-2358 www.sparksbelting.com