



Belt Name:
Sparlon 5E QM Grey


Part #:
04-702

Technical Data

| | | | |
|-----------------------------------|----------------------|-----------|-------|
| Color | Grey | | |
| Compound | Elastomer | | |
| Plies | 1 | | |
| Fabric/Carcass | Polyester | | |
| Cover Surface | Elastomer | | |
| Hardness | 75 Durometer Shore A | | |
| Bottom Surface | Elastomer | | |
| Recommended elongation at fitting | .3 to 2% | | |
| Working Strength | 114# @ 1% | | |
| Overall Gauge | .196" | | |
| Weight per Sq Ft | 1.13# | | |
| Minimum Pulley Normal-180° | 1.96" | Back Flex | 1.96" |
| Temp Range °F | -4°F to 176°F | | |
| Food Approved | No | | |
| Anti-Static | Yes | | |
| Recommended Splice | Finger | | |
| Clipper Lace | N/A | | |
| Alligator Lace | N/A | | |
| Maximum Width | 19.6" | | |

Features/Benefits:

Excellent resistance to oils, inks, chemicals and abrasion. This belt is non-marking, offers permanent antistatic characteristics and provides high flexibility and dimensional stability. The quick finger splice is ideal for applications where downtime must be kept to an absolute minimum. Ideal for folder gluer machines and production lines in the corrugated industry. Also suited for printing industry and tube winder applications in the corrugated industry. Commonly used on Flexo Folder Gluers.



Phone: (800) 451-4537 Fax: (800) 338-2358 www.sparksbelting.com

6/28/2022