



**Belt Name:**  
**3 Ply 330 SBR 1/4 x 1/16**

**Part #:**  
**39S41/02-012**

**Technical Data**

Color	Black		
Compound	SBR Styrene-butadiene		
Plies	3		
Fabric/Carcass	Polyester/Nylon		
Cover Surface	1/4" Smooth		
Hardness	60 Durometer		
Bottom Surface	1/16" Smooth		
Working Strength	330		
Overall Gauge	0.483", 31/64" , 12.27 mm		
Weight per Sq Ft	3.04		
Minimum Pulley	60-80% tension	Back Flex	60-80% tension
Normal-180°	12"		12"
Temp Range °F	-20° to 250°		
Food Approved	No		
Anti-Static	No		
Recommended Splice	Laced 140, 190, R5, 550, 2	Vulcanized Step length (bias)	6-8"
Clipper Lace	N/A		
Alligator Lace	N/A		
Maximum Width	72"	Max width stocked	60"

**Features/Benefits:**

1/4" top cover adds life in abrasive applications. General purpose abrasion resistant belting used to carry items such as stone, sand, lump materials, recyclables, or material that requires abrasion resistant belting. Common industries: Crushed Stone, Concrete Recycle Processor, Brick and Block Production. Not good for oily applications. Good abrasion resistance. Recommend use on roller bed conveyors



