



Belt Name:

Part #:

3 Ply 330 SBR 3/16 x 1/16 39S31/02-062

Technical Data

Color	Black		
Compound	SBR Styrene-butadiene		
Plies	3		
Fabric/Carcass	Polyester/Nylon		
Cover Surface	3/16" Smooth		
Hardness	60 Durometer		
Bottom Surface	1/16" Smooth		
Working Strength	330		
Overall Gauge	0.405", 13/32" , 10.3 mm		
Weight per Sq Ft	2.5		
Minimum Pulley	60-80% tension	Back Flex	60-80% tension
Normal-180°	12"		12"
Temp Range °F	-20° to 250°		
Food Approved	No		
Anti-Static	No		
Recommended Splice	Laced 140, 190, R5, 550	Vulcanized	Step length (bias) 6-8"
Clipper Lace	N/A		
Alligator Lace	N/A		
Maximum Width	84"	Max width stocker 60"	

Features/Benefits:

General purpose abrasion resistant belting used to carry items such as stone, sand, tramp materials, recyclables, or material that requires abrasion resistant belting. Common industries: Crushed Stone, Concrete Recycle Processor, Brick and Block Production. Not good for oily applications. Good abrasion resistance. Recommend use on roller bed conveyors.



5/18/2015