



Belt Name:  
**220 COS x BB**

Part #:  
**02-530**

**Technical Data**

|                      |                |    |              |
|----------------------|----------------|----|--------------|
| Color                | Black          |    |              |
| Compound             | Rubber         |    |              |
| Plies                | 2              |    |              |
| Fabric/Carcass       | Polyester      |    |              |
| Cover Surface        | .045" Smooth   |    |              |
| Hardness             | 60 Durometer   |    |              |
| Bottom Surface       | Bare           |    |              |
| Coefficient/Friction | 0.25           |    |              |
| Working Strength     | 220 lbs.       |    |              |
| Overall Gauge        | .150"          |    |              |
| Weight per Sq Ft     | .85 lbs.       |    |              |
| Minimum Pulley       | Normal-180°    | 3" | Back Flex 5" |
| Temp Range °F        | -40° to 225° F |    |              |
| Food Approved        | No             |    |              |
| Anti-Static          | No             |    |              |
| Recommended Splice   | Step Lap       |    |              |
| Clipper Lace         | # 2            |    |              |
| Alligator Lace       | # 20           |    |              |
| Maximum Width        |                |    |              |

**Features/Benefits:**

Avoid oil, grease, and solvents. Treated carcass increases ply adhesion and decreases edge curl. Inexpensive option for horizontal case and package handling in warehouses and airports. This belt offers product grip and has heavy skims between the plies for desired bulk and impact resistance.



