



Belt Name:
MF BLU 212 AM

Part #:
03-710

Technical Data

| | |
|----------------------|---|
| Color | Blue |
| Compound | Anti-Microbial Polyurethane |
| Plies | 2 |
| Fabric/Carcass | Non-Fray Polyester |
| Cover Surface | Matte |
| Hardness | 85 Durometer Shore A |
| Bottom Surface | Negative Diamond |
| Coefficient/Friction | 0.2 |
| Working Strength | 40# @ 1% |
| Overall Gauge | .083" |
| Weight per Sq Ft | .47# |
| Minimum Pulley | |
| Normal-180° | 1.18" Back Flex 1.18" |
| Temp Range °F | -4° F to 212° F |
| Food Approved | Yes |
| Anti-Static | No |
| Recommended Splice | Finger |
| Clipper Lace | 36XP |
| Alligator Lace | #1 or #62 |
| Maximum Width | 126" |

Features/Benefits:

Food approved urethane with anti microbial inhibitor in compound for use in food applications. Negative diamond on pulley side provide protection for bacteria and at the same time allow to be used with roller and slider beds alike. Great belt for capped edges. Applications include fruit/vegetable, fish/poultry and meats and cheese and dairy.



Phone: (800) 451-4537 Fax: (800) 338-2358 www.sparkselting.com

6/28/2022